

# **TORLYS**

## **smart floors**

### **MATERIAL SAFETY DATA SHEET**

**Date Prepared**      November 10, 2006

#### **Identification**

Product Name:                      **TORLYS EVEREST**

Supplier Name :            TORLYS Inc., 1900 Derry Road East, Mississauga, Ontario L5S 1Y6  
Ph: 800 461-2573  
Fx: 800 461-5220

#### **Product Description**

Veneered floating floor panels

#### **Definition**

Panels of flooring for loose laid installation formed by a top layer of a wood veneer ( 0.6 mm), a coating, a middle layer of 12mm wood fiberboard, one back layer of a wood veneer ( 0.6 mm ), and a backing layer of agglomerated cork (2mm) The panels of flooring have tongue and groove edges for secure and perfect floating installation

#### **Composition**

- 1) Poly-urethane Ultra Violet cured lacquer
- 2) Multi component glue (Or Solvent Free PVA glue)
- 3) Hardwood veneer
- 4) Wood fiberboard
- 5) Agglomerated cork

#### **Hazards Identification**

Solid material, manual or mechanical cutting can result in the generation of wood and cork dust. Wood and cork dust can cause nasal dryness, irritation and obstruction. Wood veneer floating floors have extremely low concentration of volatile compounds. HDF boards are of the lowest class (E1) of Formaldehyde content. Exposure to formaldehyde vapors can cause temporary irritation of skin, eyes or respiratory systems in susceptible individuals.

#### **First- Aid Measures**

**Inhalation:** Remove to fresh air. Get medical advice if persistent irritation or breathing difficulty occurs

**Ingestion:** Not applicable

**Eye contact:** irrigate immediately with water for at least 5 minutes. Consult a physician if symptoms persist.

**Skin:** Not applicable

# **TORLYS**

## **smart floors**

### **Fire behavior**

Wood veneer floors do not present any special risk and are not explosion hazard products. Sanding or sawing can result in the generation of wood or cork dust that can present an explosion hazard if a dust cloud contacts an ignition source.

Water, carbon dioxide and chemical powder and foam can be used as extinguishing media.

The same fire fighting procedures as for wood are applicable. Use protective clothing and self-contained breathing apparatus.

### **Packing**

Wood veneer floor panels are dispatched in packages that provide suitable protection, and which are sufficiently watertight to keep the moisture content of the floor as specified under normal storage conditions.

### **Handling and Storage**

Wear safety glasses when machining the product. Other protective equipment such as gloves or respirators may be needed depending on dust conditions

For transport purpose, the product is not qualified as dangerous.

Store at normal room temperature in a dry and ventilated area.

### **Ecological and disposal information**

If correctly used, no environmental harmful effects are to be expected. Disposal according to local legislation. If possible recycle the product. It may be incinerated.

### **Other information**

The information on this MSDS represents our best present knowledge and is given in good faith but without warranty. It remains the users responsibility to make sure that the information is appropriate and complete for his special use of the product

✉ **Torlys National Call Centre Location**  
1900 Derry Road E., Mississauga, ON L5S 1Y6

PH: 905-612-8772 800-461-2573  
FAX: 905-612-9049 800-461-5220

✉ **Torlys British Columbia Location**  
1292 Cliveden Avenue, Delta, British Columbia,  
V3M 6G4 Canada

PH: 604-777-9744  
FAX: 604-777-9766